

EC1260BL

Combination Blanket/Fluid Warming Cabinet



**12.6 ft³ (0.36m³)
interior capacity**

Windowed doors

Interior illumination

Deluxe electronic control

**Seismic wall mount
bracket kit is OSHPD
approved (#OPM-0067-13)**

Fluid chamber

WarmRight[®] provides the right temperature for the right product: irrigation (IRR) or injection (INJ) fluids

Temperature range

37°-66°C (98°-150°F)
adjustable irrigation mode

37°-40°C (98°-104°F)
adjustable injection mode

Blanket chamber

37°-93°C (98°-200°F)
temperature range

24-hour timer (single
programmable "off" period)

Epoxy-coated blanket
support assembly

EC1260BL Combination Blanket/Fluid Warming Cabinet

Specifications:

This warming cabinet is designed to safely warm and store blankets and either irrigation fluids or injection fluids.

The dual-chambered warming cabinet is constructed with stainless steel exterior casing and door with handle and hinges designed to withstand heavy usage. A door with window allows observation of inventory with the door closed. The cabinet is warmed using low-heat-density electrothermal cable array. The electrothermal cable is positioned in the floor and two sides of the warming cabinet, providing even heating of the interior chamber.

The blanket warming chamber includes a white, epoxy-coated blanket support assembly and two (2) shelves. The fluid warming chamber is equipped with one (1) white, epoxy-coated shelf to accommodate most commonly used surgical fluids packaged in bags or bottles. The basket has a capacity of **18 1-liter bottles or 28 1-liter bags**. The cabinet is furnished with four (4) leveling feet.

Control:

Each chamber's temperature is regulated by a separate electronic control consisting of a 4 digit L.E.D. display, ON/OFF button, INCREASE and DECREASE buttons, integrated lock-out control feature and a series of prompt sequence indicators.

Each control can easily be set to operate in Fahrenheit or Celsius. After a power failure, the cabinet will remember its programming and begin to operate as before. The ON/OFF indicator will blink to indicate a failure occurred; pressing the ON/OFF button once will eliminate this blinking. A thermal shut-off system, separate from the electronic controls, is included as an additional safety feature.

The control will display temperature in whole degrees.

Blanket warming chamber:

The design and operational characteristics of the chamber eliminate the need for a heat circulating fan.

The electronic control has an adjustable temperature range of 37° to 93°C (98° to 200°F).

The TIMER feature allows the user to program the control to automatically turn on and turn off once during a 24 hour period at selected times. This enables the chamber to be shut off automatically at night to save energy, but to turn on again in the early morning to ensure warm blankets are available.

Fluid warming chamber:

The warming cabinet can be programmed to warm either irrigation fluids (IRR) or injection fluids (INJ), with separate temperature ranges provided depending on the choice selected.

- IRR temperature range: 37° to 66°C (98° to 150°F),
- INJ temperature range: 37° to 40°C (98° to 104°F).


A fan located inside the chamber mixes the air to prevent temperature stratification and to ensure an accurate chamber temperature for each mode.

- Within +0/-1.67°C (+0/-3°F) for set points of 43° to 66°C (110° to 150°F)
- Within +0/-1.12°C (+0/-2°F) for set points of 37° to 40°C (98° to 104°F).

An alarm will sound if temperatures exceed 6°C (10°F) over the set-point temperature, and an OVERTEMP indicator will blink indicating an over-temperature condition.

Special Information:

- Right hinging is standard.
Left hinging is available as a special order.
- Windowed door is standard.
Solid door is available as a special order.
- WarmWatch® available as special order.



Capacity and Weights	
Interior Capacity (PER COMPARTMENT)	
Fluid compartment	18 1-liter bottles or 28 1-liter bags
Blanket compartment	8.7 cubic feet (0.25 m ³)
Net Weight	320 lb (145 kg)
Ship Weight	420 lb (191 kg)

Electrical	
120 V.A.C. — 50/60 Hz, 1 ph 1.7 kW, 14.2 Amps Safety Class I Equipment No Applied Parts Mode of Operation: Continuous	
230 V.A.C. — 50/60 Hz, 1 ph 1.58 kW, 6.9 Amps Type B Equipment	

*Other international plugs are available, contact factory for more information.

Options and Accessories	
Bracket Kit for Seismic Wall Mount (OPM-0067-13) {special installation requirements apply; see Bracket Kit spec }	CONTACT FACTORY
Built-in Trim Kit	5013968
Combination Lock	5008361
Lock for Door Handle	LK-22567



ENTHERMICS MEDICAL SYSTEMS

An ISO 13485:2003 certified company

PO Box 443, Menomonee Falls WI 53052-0443
W164 N9221 Water St, Menomonee Falls WI 53051
Tel 262-251-8356 | 800-TO-B-WARM
generalinfo@enthermics.com
www.enthermics.com